



short facts

Performance

Max.diameter hardwood (in cm) (in cm)	45
Max.diameter softwood (in cm) (in cm)	56
Output approx. (in srm)	220

Intake opening

Feeding weidth (in mm)	1400
Feeding hight (in mm)	680

Grinding unit

Rotor diameter (in mm)	820
------------------------	-----

Material outfeed

Blower outfeed	✓
Conveyor belt outfeed	-

Main drive

Diesel engine	
Electric motor (in kW/PS)	-
Power requirement (in kW)	132 - 350

Carriage

Number of axes	2
Top speed (in km/h)	80

Weight (without crane)

Weight basic model (in kg)	14500
Permitted axle load (in kg)	16000
Permitted support load (in kg)	2500
Permitted total weight (in kg)	18500

Measurements transport position

Length (in mm)	6650
Width (in mm)	2550
Height (in mm)	4000

Control system

easy2	✓
easygreen	-
DIP	✓
Sensotronic	-
Automatic overload control unit	✓
Infeed speed stepless adjustable	✓
Wire-remote control	-
15-channel remote control	-
Z-Tronic	✓

HEM 593 Z



Application

- ideal machine for processing of especially bulky shrubs
- drive via power takeoff shaft with large tractors between 132 to 350 kW

Specifics

- chipper model with the widest draw-in table (1.40 m) for processing of especially bulky material
- aggressive upper draw-in roller for better draw-in behaviour
- extra-large screen area for best chipping quality
- compact dimensions and comparably low wight
- enormous screen basket cover swivel capability for optimal accessibility of rotor and screen basket changing without tools
- material outfeed via hydraulic blower or conveyor belt

JENZ GmbH Maschinen- und Fahrzeugbau

Wegholmer Str. 14
D-32469 Petershagen

Tel.: +49 (0) 5704/9409-0
E-Mail: info@jenz.de