



short facts

Performance

Max.diameter hardwood (in cm) (in cm)	42
Max.diameter softwood (in cm) (in cm)	56
Output approx. (in srm)	150

Intake opening

Feeding width (in mm)	1000
Feeding height (in mm)	650

Grinding unit

Rotor diameter (in mm)	820
Number of blades (half / full equipment) (in cm)	10 (20)

Material outfeed

Blower outfeed	✓
Conveyor belt outfeed	-

Main drive

Diesel engine	OM 471 LA
Electric motor	-
(in kW/PS)	360 / 490
Power requirement (in kW)	-

Carriage

Number of axles	-
Top speed (in km/h)	1

Weight (without crane)

Weight basic model (in kg)	18500
Permitted axle load (in kg)	-
Permitted support load (in kg)	-
Permitted total weight (in kg)	-

Measurements transport position

Length (in mm)	6500
Width (in mm)	2550
Height (in mm)	3400

Control system

easygreen	✓
DIP	✓
Sensotronic	✓
Automatic overload control unit	✓
Infeed speed stepless adjustable	✓
Wire-remote control	✓
15-channel remote control	-
Z-Tronic	-



Application

- shrubs and standing timber up to approx. 560 mm diameter
- deployment on extreme terrain and difficult soils
- flexible working on both sides
- high-powered chipping independent of towing vehicle

Specifics

- driver via high-powered add-on motor
- pivoted chipper
- generously-dimensioned longitudinal draw-in makes processing bulky material easier
- caterpillar tracks for deployment on extreme terrain
- cable remote control problem-free
- transport on low loaders

JENZ GmbH Maschinen- und Fahrzeugbau

Wegholmer Str. 14
D-32469 Petershagen

Tel.: +49 (0) 5704/9409-0
E-Mail: info@jenz.de