



## short facts

### Performance

Max.diameter hardwood (in cm) (in cm)	45
Max.diameter softwood (in cm) (in cm)	56
Output approx. (in srm)	200

### Intake opening

Feeding width (in mm)	1200
Feeding height (in mm)	680

### Grinding unit

Rotor diameter (in mm)	820
Number of blades (half / full equipment) (in cm)	12 (24)

### Material outfeed

Blower outfeed	✓
Conveyor belt outfeed	-

### Main drive

Diesel engine	MAN, Euro 6c
Electric motor	-
(in kW/PS)	368/500
Power requirement (in kW)	-

### Carriage

Number of axles	3
Top speed (in km/h)	80

### Weight (without crane)

Weight basic model (in kg)	25000
Permitted axle load (in kg)	25000
Permitted support load (in kg)	-
Permitted total weight (in kg)	25000

### Measurements transport position

Length (in mm)	7700
Width (in mm)	2550
Height (in mm)	4000

### Control system

easygreen	✓
DIP	✓
Sensotronic	-
Automatic overload control unit	✓
Infeed speed stepless adjustable	✓
Wire-remote control	-
15-channel remote control	-
Z-Tronic	-



### Application

- shrubs and standing timber up to approx. 560 mm diameter
- ideal for working in restricted spaces
- large deployment radius

### Specifics

- optimized successor model of the bestseller HEM 582 R-Truck
- chipper drive via HGV motor
- extra-large screen area for best chipping quality
- enormous screen basket cover swivel capability for optimal accessibility of rotor and screen basket changing without tools
- optimised draw-in table for continuous material draw-in
- material outfeed via hydraulic blower can be fitted centrally between driver's cab and chipper cell on request
- comfortable working position
- compact dimensions, low weight and small turning circle
- 80 km/h top speed

## JENZ GmbH Maschinen- und Fahrzeugbau

Wegholmer Str. 14  
D-32469 Petershagen

Tel.: +49 (0) 5704/9409-0  
E-Mail: [info@jenz.de](mailto:info@jenz.de)