



short facts

Performance

Max.diameter hardwood (in cm) (in cm)	45
Max.diameter softwood (in cm) (in cm)	56
Output approx. (in srm)	220

Intake opening

Feeding width (in mm)	1400
Feeding height (in mm)	680

Grinding unit

Rotor diameter (in mm)	820
Number of blades (half / full equipment) (in cm)	14 (28)

Material outfeed

Blower outfeed	✓
Conveyor belt outfeed	-

Main drive

Diesel engine	MAN, Euro 6c
Electric motor	-
(in kW/PS)	368/500
Power requirement (in kW)	-

Carriage

Number of axles	3
Top speed (in km/h)	80

Weight (without crane)

Weight basic model (in kg)	27000
Permitted axle load (in kg)	27000
Permitted support load (in kg)	-
Permitted total weight (in kg)	27000

Measurements transport position

Length (in mm)	7954
Width (in mm)	2550
Height (in mm)	4000

Control system

easygreen	✓
DIP	✓
Sensotronic	-
Automatic overload control unit	✓
Infeed speed stepless adjustable	✓
Wire-remote control	-
15-channel remote control	-
Z-Tronic	-

HEM 593 R Cobra



Application

- shrubs and standing timber up to approx. 560 mm diameter
- alternative to tractor with power takeoff shaft chipper
- ideal machine for medium to large jobs
- ideal for working in restricted spaces
- large deployment radius

Specifics

- chipper drive via HGV motor
- rotating (Cobra) driver's cab for best overview
- HGV can also be relocated with rotated cab and full carrier vehicle tractive force
- chipper series with widest draw-in table (1.40 m) makes processing of bulky material and thick trunks easier
- material outfeed using centric hydraulic blower
- optimised draw-in table for continuous material draw-in
- enormous screen basket cover swivel capability for optimal accessibility of rotor and screen basket changing without tools
- extremely large screen area for best chipping quality
- 80 km/h top speed

JENZ GmbH Maschinen- und Fahrzeugbau

Wegholmer Str. 14
D-32469 Petershagen

Tel.: +49 (0) 5704/9409-0
E-Mail: info@jenz.de