



Short Facts

Performance

Max diameter hardwood (in cm) (in cm)	42
Max diameter softwood (in cm) (in cm)	56
Output approx. (in srm)	120
Power requirement (in kW)	100 - 235

Intake opening

Feeding width (in mm)	1000
Feeding height (in mm)	650

Grinding unit

Rotor diameter (in mm)	820
Number of blades (half / full equipment) (in cm)	10 (20)

Material outfeed

Blower outfeed	-
Conveyor belt outfeed	-

Main drive

Diesel engine	-
Electric motor	-
(in kW/PS)	-

Carriage

Number of axles	2
Top speed (in km/h)	80

Weight (without crane)

Weight basic model (in kg)	9600
Permitted axle load (in kg)	13000
Permitted support load (in kg)	1000
Permitted total weight (in kg)	14000

Measurements transport position

Length (in mm)	5920
Width (in mm)	2550
Height (in mm)	3600

Control system

easygreen	✓
DIP	✓
Sensotronic	
Automatic overload control unit	✓
Infeed speed stepless adjustable	✓
Wire-remote control	-
15-channel remote control	-
Z-Tronic	✓

HEM 561 Z



Application

- shrubbery and trunk wood up to approx. 560 mm diameter
- driven by PTO shaft with tractors of 100 to 265 kW

Specifics

- manageable acquisition and operation costs
- large screening surface for best chip quality
- Low empty weight

JENZ GmbH Maschinen- und Fahrzeugbau

Wegholmer Str. 14
D-32469 Petershagen

Tel.: +49 (0) 5704/9409-0
E-Mail: info@jenz.de