

Short Facts

Performance

Max.diameter hardwood (in cm) (in cm)	45
Max.diameter softwood (in cm) (in cm)	56
Output approx. (in srm)	200

Intake opening

Feeding weidth (in mm)	1200
Feeding hight (in mm)	680

Grinding unit

Rotor diameter (in mm)	820
Number of blades (half / full equipment) (in cm)	12 (24)

Material outfeed

Blower outfeed	✓
Conveyor belt outfeed	-

Main drive

Diesel engine	-
Electric motor	-
(in kW/PS)	-
Power requirement (in kW)	132 - 350

Carriage

Number of axles	2
Top speed (in km/h)	80

Weight (without crane)

Weight basic model (in kg)	11200
Permitted axle load (in kg)	16000
Permitted support load (in kg)	2000
Permitted total weight (in kg)	18000

Measurements transport position

Length (in mm)	6240
Width (in mm)	2550
Height (in mm)	3700

Control system

easygreen	✓
DIP	✓
Sensotronic	-
Automatic overload control unit	✓
Infeed speed stepless adjustable	✓
Wire-remote control	-
15-channel remote control	-
Z-Tronic	✓

HEM 583 Z



Application

- shrubs and standing timber up to approx. 560 mm diameter
- drive via power takeoff shaft with large tractors between 132 to 350 kW

Specifics

- optimised draw-in table for continuous material draw-in
- aggressive upper draw-in roller for better draw-in behaviour
- extra-large screen area for best chipping quality
- compact dimensions and comparably low wight
- enormous screen basket cover swivel capability for optimal accessibility of rotor and screen basket changing without tools
- material outfeed via hydraulic blower or conveyor belt

JENZ GmbH Maschinen- und Fahrzeugbau

Wegholmer Str. 14
D-32469 Petershagen

Tel.: +49 (0) 5704/9409-0
E-Mail: info@jenz.de