



short facts

Performance

Max.diameter hardwood (in cm) (in cm)	60
Max.diameter softwood (in cm) (in cm)	80
Output approx. (in srm)	300

Intake opening

Feeding weidth (in mm)	1400
Feeding hight (in mm)	820

Grinding unit

Rotor diameter (in mm)	1040
------------------------	------

Material outfeed

Blower outfeed	✓
Conveyor belt outfeed	-

Main drive

Diesel engine	
Electric motor (in kW/PS)	-
Power requirement (in kW)	180 - 400

Carriage

Number of axes	2
Top speed (in km/h)	80

Weight (without crane)

Weight basic model (in kg)	18.500
Permitted axle load (in kg)	18.000
Permitted support load (in kg)	2700
Permitted total weight (in kg)	22.000

Measurements transport position

Length (in mm)	6960
Width (in mm)	2550
Height (in mm)	4000

Control system

easy2	✓
easygreen	-
DIP	✓
Sensotronic	-
Automatic overload control unit	✓
Infeed speed stepless adjustable	✓
Wire-remote control	-
15-channel remote control	-
Z-Tronic	✓

HEM 841 Z



- shrubs and standing timber up to approx. 800 mm diameter
- drive via power takeoff shaft with tractors between 150 and 400 kW
- ideal machine for medium to large jobs

Specifics

- low wear costs due to hydraulic blower
- extremely large screen area for best chipping quality
- optimised draw-in table for continuous material draw-in
- enormous screen basket cover swivel capability for optimal accessibility of rotor and screen basket changing without tools
- material outfeed via hydraulic blower or conveyor belt
- largest power takeoff drive mobile chipper from JENZ

JENZ GmbH Maschinen- und Fahrzeugbau

Wegholmer Str. 14
D-32469 Petershagen

Tel.: +49 (0) 5704/9409-0
E-Mail: info@jenz.de