MULCHERS FOR MINI LOADERS

BL0/ML

Mulcher for mini track loaders and articulated mini loaders from 24 to 40 hp.

The BL0/ML forestry mulcher, specially designed for mini track loaders and articulated mini loaders from 24 to 40 hp, can mulch light vegetation, brush and trees up to 10 cm in diameter. Bite Limiter technology delivers high productivity and consistently efficient mulching. The gear motor, which does not require a dedicated case drain line, minimizes routine maintenance. The Spike PRO counter blades reduce power absorption and produce a finer end product. The BL0/ML can be equipped with BL/MINI blades or C/3/MINI teeth.

24-40 hp

45-70 L/min

10 cm





Spike Pro interchangeable counter blades
for finer mulched material

Rotor with Bite Limiter technology
maximum productivity with minimum power thanks to the special high-resistance steel inserts and BL/MINI blades



Gear motor with no case drain required

Adjustable and interchangeable skids

STANDARD EQUIPMENT

16 cc-gear hydraulic motor	Interchangeable protection chains
Flow Control system valve with integrated safety and anticavitation valves	Interchangeable bolt-on Spike PRO counter blades
Motor enclosed in the frame	Interchangeable forged steel rotor shafts
Enclosed, dust-resistant machine body	Adjustable skids
Hydraulic hoses	Deflector
Trapezoidal belts transmission	Mechanically adjustable push frame
Bite Limiter rotor with blades BL/MINI	

OPTIONS

Adaptor plate from CII to Mini-SAE	Operator protection for mini loaders
Multiple tooth options	

MODEL	BL0/ML-70	BL0/ML-100
Engine (hp)	24-40	24-40
Flow rate (L/min)	45-70	45-70
Pressure (bar)	160-250	160-250
Working width (mm)	700	1000
Total width (mm)	907	1213
Weight (kg)	285	350
Max shredding diameter (mm)	100	100
Rotor diameter (mm)	310	310
No. blade type BL/MINI	12	20

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions.

MAIN ACCESSORIES



Lexan windshield
protects the operator from the direct or indirect impact of airborne material



Adapter plate
for converting the standard CII mounting plate to a Mini-SAE mount



BLADE BL/MINI
(standard)



TOOTH C/3/MINI
(option)